Table of Contents

RenderLdapUser.....1
Description.....1
Parameters.....1
Implementation.....1
Test.....1

RenderLdapUser

Description

Extract user information from an Ldap directory. Note, you have to install the LdapNgPlugin to make this work. Depending on your directory layout and the used schema you have to adjust the filter below.

Parameters

- KEY: key used to fetc the user record, e.g. the login name

Implementation

Guest users should not see login name.

```
%STARTINCLUDE%
%IF{"'%USERNAME%'!='guest'" then='%LDAP{"(&(objectClass=person)(uid=%KEY%))"
   clear="$cn,$mail,$departmentNumber,$telephoneNumber,$postalAddress,$labeledURI"
   limit="1"
   format="
       <b>Login</b>: $cn
       <b>Email</b>: $mail
       <b>Tel:</b> $telephoneNumber
       <b>Address:</b> <br> $postalAddress "}%'
}%
%IF{"'%USERNAME%'='guest'" then='%LDAP{"(&(objectClass=person)(uid=%KEY%))"
   clear="$cn,$mail,$departmentNumber,$telephoneNumber,$postalAddress,$labeledURI"
   limit="1"
   format="
       <b>Email</b>: $mail
       <b>Tel:</b> $telephoneNumber
       <b>Address:</b> <br> $postalAddress "}%'
}%
%STOPINCLUDE%
```

Test

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions

Topic revision: r3 - 28 Aug 2010 - 13:06:35 - UrsBeyerle

- . Main
- Log In

- **Main Web**
- Create New Topic
- Index
- Search
- Changes
- Notifications
- RSS Feed
- Statistics
- Preferences
- **Webs**
- Public
- System

Copyright © by the contributing authors. All material on this collaboration platform is the property of the contributing authors.
Ideas, requests, problems regarding Wiki? Send feedback