

Table of Contents

Calendar Plugin.....	1
Syntax Rules.....	1
Attributes recognized.....	1
Event Syntax.....	3
Event formatting.....	4
Multi-Day Event Formatting.....	5
Other sources of calendars.....	6
Examples.....	6
Settings.....	6
Installation Instructions.....	6
Info.....	7

Calendar Plugin

The CalendarPlugin handles the macro **%CALENDAR%** that inserts a monthly calendar in the page. Multiple topics can be specified as the source of the events, and these can be in any web. The calendar marks dates corresponding to the events. Events can be listed literally in the topics, or can be taken from the results of macro expansions (such as %SEARCH).

NOTE since release 2.000, the plugin now respects access controls on topics containing events. You must have VIEW permission on these topics to be able to see the events they contain.

Also since 2.000, preferences settings **in this topic** are no longer read. Please define preferences as non-plugin preference settings instead.

Syntax Rules

You type	you get
%CALENDAR%	a monthly calendar for the current month/year, with events taken from the current topic
%CALENDAR{<attributes>}%	is the full syntax

Attributes recognized

Attribute	Meaning▼	Default
width="n" or "n%"	Width of calendar table in pixels or percent	Minimum width needed
web="Webname"	Web containing the event topic	The current web
vcellalignment="middle"	Vertical cell alignment of day cells: "top", "middle", "bottom", "baseline"	"top"
topic="Web.TopicName1, Web.TopicName2"	Topics containing events	The topics containing the events. You must have VIEW access to these topics or the events therein will be ignored.
topic="TopicName"	Topic containing events	The topic containing the tag
gmtoffset="+/-hh"	Timezone expressed as number of hours offset from GMT	Server timezone
year="yyyy"	The year	Current year
month="mm"	The month	Current month
header="..."	Text at the top of the calendar; use \$m for current month, \$y for year	Current month and year
day	Specifies the first day to show. Only valid if aslist=1.	1
months	Specifies how many months of calendars to display. Only valid if aslist=0.	1
days	Specifies how many days of calendar data to list. Only valid if aslist=1.	1
multidayformat	Specifies formatting of the description for multi-day events. See Multi-Day Event Formatting for details.	\$description
datenumbersformat		

Attribute	Meaning	Default
	Specifies formatting for the date number in each cell. The formatting codes accepted are the same as those for the %GMTIME% variable.	'\$day' (if aslist=0) ' * \$day \$mon \$year' (if aslist=1)
todaydatenumformat	Specifies formatting for the date number for the current day (today) in the calendar. The formatting codes accepted are the same as those for the %GMTIME% variable.	datenumformat
showweekdayheaders="1"	Show the weekday headers	"0"
showdatenumbers="0"	Show day numbers 1...31 in date cells. Note that showdatenumbers=1 means that HTML::CalendarMonthSimple will add the date numbers to the cells. If showdatenumbers=0, then the plugin adds the date numbers. The result of this is that a calendar will always show the date numbers.	"0" (except with aslist="1", see below)
year="+yy" or "-yy"	Relative year	Current year
month="+mm" or "-mm"	relative month	Current month
nowrap="1" or "0"	Prevent cell content from wrapping	"0"
lang="language"	Language: First few characters of "English", "Français", "Deutsch", "Español", "Português", "Nederlands", "Italiano", "Norsk", "Svenska", "Dansk", "suomi", "Magyar", "Polski	"English"
weekdayheadersbig="0"	If enabled, show weekday headers in bold cell headings	"1"
format="..."	How to highlight a date. NOTE make sure you use \$old to denote the date output, otherwise you may only see one event per day.	See Event Formatting below
cellalignment="left"	Horizontal cell alignment of day cells: "left", "center", "right", "justify", "char"	"center"
cellheight="n"	Height in pixels of each cell in the calendar	Minimum height needed
weekstartsonmonday="1" or "0"	Flag to start week on Monday	"0" (Sunday)
contentcolor="#nnnn"	Default content color of all cells unless redefined	black
bgcolor="#nnnn"	Default background color of all cells unless redefined by other color settings below (use an HTML color-code like "#000000" as defined in StandardColors)	white
daynames="Mon Tue ..."	Custom day names	"Monday Tuesday Wednesday Thursday Friday Saturday Sunday"
weekendcellclass	css class given to weekend in the showweekdayheaders	weekend

Attribute	Meaning	Default
weekdaycellclass	css class given to weekdays in the showweekdayheaders	weekday
todaycellclass	css class given to today's element (in addition to cellclass)	today
tableclass	css class given to the outer table	calendar \$month \$year
headerclass	css class given to the header	calendarHeader
cellclass	css class given to each day's element	day \$day \$month \$year
aslist	Controls whether events displayed in calendar style (aslist=0) or list style (aslist=1). Note that specifying aslist=1 forces showdatenumbers=1 and defaults to show <i>only</i> one day's events (see day and days). This is done to ensure that the date number is formatted according to datenumberformat and that only the days that have an event are listed.	0
weekendheadercontentcolor="#nnnn"	Content color of weekends' headers	contentcolor setting
weekendcontentcolor="#nnnn"	Content color of weekend cells	contentcolor setting
weekdayheadercontentcolor="#nnnn"	Content color of weekdays' headers	contentcolor setting
weekdaycontentcolor="#nnnn"	Content color of weekday cells	contentcolor setting
todaycontentcolor="#nnnn"	Content color of today's cell	contentcolor setting
headercontentcolor="#nnnn"	Content color of the Month+Year header	contentcolor setting
border="n"	Border width of calendar table	"1"
weekendcolor="#nnnn"	Background of weekend cells	light gray
todaycolor="#nnnn"	Background of today's cell	The web bgcolor
weekendheadercolor="#nnnn"	Background color of weekends' headers	bgcolor setting
weekdayheadercolor="#nnnn"	Background color of weekdays' headers	bgcolor setting
weekdaycolor="#nnnn"	Background color of weekday cells	bgcolor setting
headercolor="#nnnn"	Background color of the Month+Year header	The web bgcolor
eventbgcolor	Background color Event, when have a event in calendar	for default is undef, you have to put son color

and other attributes of HTML::CalendarMonthSimple

Event Syntax

Events are defined by bullets with the following syntax:

Event type	Syntax	Example
Single:	* dd MMM yyyy - description	09 Dec 2002 - Expo
Interval:	* dd MMM yyyy - dd MMM yyyy -	02 Feb 2002 - 04 Feb 2002 - Vacation

Event type	Syntax	Example
	description	
Yearly:	* dd MMM - description	05 Jun - Every 5th of June
	* w DDD MMM - description	2 Tue Mar - Every 2nd Tuesday of March
	* L DDD MMM - description	L Mon May - The last Monday of May
	* A dd MMM yyyy - description	A 20 Jul 1969 - First moon landing This style will mark anniversaries of an event that occurred on the given date. The description will have " (x)" appended to it, where "x" indicates how many years since the occurrence of the first date. The first date is not annotated.
Monthly:	* w DDD - description	1 Fri - Every 1st Friday of the month
	* L DDD - description	L Mon - The last Monday of each month
	* dd - description	14 - The 14th of every month
Weekly:	* E DDD - description	E Wed - Every Wednesday
	* E DDD dd MMM yyyy - description	E Wed 27 Jan 2005 - Every Wednesday Starting 27 Jan 2005
	* E DDD dd MMM yyyy - dd MMM yyyy - description	E Wed 1 Jan 2005 - 27 Jan 2005 - Every Wednesday from 1 Jan 2005 through 27 Jan 2005 (inclusive)
Periodic:	* En dd MMM yyyy - description	E3 02 Dec 2002 - Every three days starting 02 Dec 2002
	* En dd MMM yyyy - dd MMM yyyy - description	E3 12 Apr 2005 - 31 Dec 2005 - Every three days from 12 Apr 2005 through 31 Dec 2005 (inclusive)
Exception:	Insert the following between the above syntax and the description: X { dd MMM yyyy, dd MMM yyyy - dd MMM yyyy }	1 Fri X { 01 Dec 2002, 06 Dec 2002 - 14 Dec 2002 } - Every first Friday except on the 01 Dec 2002 and between 06 Dec 2002 and 14 Dec 2002

Event formatting

For a table-style calendar, each day which has one or more events will have a list of the descriptions of those events. Each event description will be set in a small font. In other words, format is:

```
$old<br /><small>$description</small>
```

For a list-style calendar, if an event falls in the selected time period, then it is displayed (by default) as a bullet item with the date as dd Mmm yyyy In other words, datenumberformat is:

```
* $day $mon $year
```

and format is:

```
$old - $description
```

This displays the events in a form very similar to that in which they are specified (although specific to a particular date).

Multi-Day Event Formatting

The `multidayformat` option allows the description of each day of a multiday event to be displayed differently. This could be used to visually or textually annotate the description to indicate continuance from or to other days.

The option consists of a comma separated list of formats for each type of day in a multiday event:

first, middle, last, middle-unseen, last-unseen

Where:

- *first* is the format used when the first day of the event is displayed
- *middle* is the format used when the day being displayed is not the first or last day
- *last* is the format used when the last day of the event is displayed
- *middle-unseen* is the format used when the day being displayed is not the first or last day of the event, but the preceding days of the event have not been displayed. For example, if an event runs from 29 Apr to 2 May and a May calendar is being displayed, then this format would be used for 1 May.
- *last-unseen* is the format used when the day being displayed is the last day of the event, but the preceding days of the event have not been displayed. For example, if an event runs from 29 Apr to 1 May and a May calendar is being displayed, then this format would be used for 1 May. Note that in the previous example (event from 29 Apr to 2 May), this format would **not** be used for a May calendar because the event was "seen" on 1 May; so, the *last* format would be used for 2 May.

Within each format, date information for the current day can be substituted using the same format codes as accepted by `%GMTIME%`. An extension to these codes allows the date of the first and/or last day of the event to also be rendered.

- `$first(format)` will render the first date of the event according to *format*, where *format* is, again, a string of codes acceptable to `%GMTIME%`.
- `$last(format)` will render the last date of the event in the way just described for `$first()`

Missing formats will be filled in as follows:

- *middle* will be set to *first*
- *last* will be set to *middle*
- *middle-unseen* will be set to *middle*
- *last-unseen* will be set to *last*

Missing formats are different from empty formats. For example,

```
multidayformat="$description (until $last($day $month)),,"
```

specifies an empty format for *middle* and *last*. The result of this is that only the first day will be shown. Note that since an unspecified *middle-unseen* is set from the (empty) *middle* format, an event that begins prior to the calendar being displayed but ending in the current calendar will not be displayed. In contrast, `multidayformat="$description"` will simply display the description for each day of the event; all days (within the scope of the calendar) will be displayed.

The default format is to simply display the description of the event.

Other sources of calendars

You can also use the Foswiki:Extensions.CalDAVPlugin to recover calendars from a CalDAV server.

Examples

You type:	You get:																																																																																																																																																		
<div>A list of Events is just a bullet list like this:</div> <div><ul style="list-style-type: none">• 2 Feb - Andrea's birthday• A 7 Mar 1966 - Nicoletta's birthday• 29 May 1996 - Maria Teresa is born!• 29 Sep 1998 - Davide is born!</div> <div><pre>%CALENDAR{month="2" year="2002" bgcolor="cyan"}% %CALENDAR{month="3" year="2002" showweekdayheaders="1"}%</pre></div>	<div><div>February 2002</div><table><tr><td></td><td></td><td></td><td></td><td></td><td>01</td><td>02</td><td colspan="7">Andrea's birthday</td></tr><tr><td>03</td><td>04</td><td>05</td><td>06</td><td>07</td><td>08</td><td>09</td><td colspan="7"></td></tr><tr><td>10</td><td>11</td><td>12</td><td>13</td><td>14</td><td>15</td><td>16</td><td colspan="7"></td></tr><tr><td>17</td><td>18</td><td>19</td><td>20</td><td>21</td><td>22</td><td>23</td><td colspan="7"></td></tr><tr><td>24</td><td>25</td><td>26</td><td>27</td><td>28</td><td></td><td></td><td colspan="7"></td></tr></table></div> <div><div>March 2002</div><table><tr><th>Sunday</th><th>Monday</th><th>Tuesday</th><th>Wednesday</th><th>Thursday</th><th>Friday</th><th>Saturday</th><th>Sunday</th><th>Monday</th></tr><tr><td></td><td></td><td></td><td></td><td></td><td>01</td><td>02</td><td></td><td></td></tr><tr><td>03</td><td>04</td><td>05</td><td>06</td><td>07</td><td>08</td><td>09</td><td>03</td><td></td></tr><tr><td>10</td><td>11</td><td>12</td><td>13</td><td>14</td><td>15</td><td>16</td><td>10</td><td></td></tr><tr><td>17</td><td>18</td><td>19</td><td>20</td><td>21</td><td>22</td><td>23</td><td>17</td><td></td></tr><tr><td>24</td><td>25</td><td>26</td><td>27</td><td>28</td><td>29</td><td>30</td><td>24</td><td></td></tr><tr><td>31</td><td></td><td></td><td></td><td></td><td></td><td></td><td>31</td><td></td></tr></table></div>																			01	02	Andrea's birthday							03	04	05	06	07	08	09								10	11	12	13	14	15	16								17	18	19	20	21	22	23								24	25	26	27	28										Sunday	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday	Sunday	Monday						01	02			03	04	05	06	07	08	09	03		10	11	12	13	14	15	16	10		17	18	19	20	21	22	23	17		24	25	26	27	28	29	30	24		31							31	
						01	02	Andrea's birthday																																																																																																																																											
	03	04	05	06	07	08	09																																																																																																																																												
	10	11	12	13	14	15	16																																																																																																																																												
	17	18	19	20	21	22	23																																																																																																																																												
	24	25	26	27	28																																																																																																																																														
	Sunday	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday	Sunday	Monday																																																																																																																																										
						01	02																																																																																																																																												
	03	04	05	06	07	08	09	03																																																																																																																																											
	10	11	12	13	14	15	16	10																																																																																																																																											
17	18	19	20	21	22	23	17																																																																																																																																												
24	25	26	27	28	29	30	24																																																																																																																																												
31							31																																																																																																																																												

Settings

Any of the recognized attributes can be overridden using preferences. These preferences all start with `CALENDARPLUGIN_` and end with the upper case name of the attribute. For example, * Set `CALENDARPLUGIN_FORMAT = $old $description` * Set `CALENDARPLUGIN_VCELLALIGNMENT = center` * Set `CALENDARPLUGIN_GMTOFFSET = +10` * Set `CALENDARPLUGIN_WEEKSTARTSONMONDAY = 0` Preferences can be set at the site, web, topic or user level. See `PreferenceSettings` for more information.

Installation Instructions

You do not need to install anything in the browser to use this extension. The following instructions are for the administrator who installs the extension on the server.

Open `configure`, and open the "Extensions" section. Use "Find More Extensions" to get a list of available extensions. Select "Install".

If you have any problems, or if the extension isn't available in `configure`, then you can still install manually from the command-line. See <http://foswiki.org/Support/ManuallyInstallingExtensions> for more help.

You should see two calendars near the Event list above and a current month calendar below (using css style section inline):

May 2024					
		01	02	03	04
05	06	07	08	09	10
11	12	13	14	15	16
17	18	19	20	21	22
23	24	25	26	27	28
29	30	31			

Info

Author:	Foswiki:Main.AndreaSterbini (and many others)
Version:	8058 (2010-07-07)
Release:	2.000
Change History:	
2.000 (30 Jun 2010):	Foswiki:Tasks.Item1841: Foswiki:Tasks.Item8421: Foswiki:Tasks.Item1546: added support for macro expansions to provide the event lists. This allows other plugins to generate data sources e.g. by including calendars from e.g. CalDAV. Restructured for maintenance and performance. Foswiki:Tasks.Item9231: Added topic permission checking. Crawford Currie http://c-dot.co.uk
12 Aug 2009:	Foswiki:Main.MarcelloBontempoSalgueiro: add <code>eventbgcolor</code> attribute for background color when day have a event
09 March 2009:	Foswiki:Main.SvenDowideit: add <code>day</code> attribute for aslist rendering so users can select a start day
28 Feb 2009:	Foswiki:Main.SvenDowideit: add css classes and parameters so that we're not so ugly anymore
10 Feb 2009:	Foswiki:Main.SvenDowideit: port to Foswiki
1.020:	TWiki:Main.DavidBright: Bug fix from TWiki:Main.MarcLangheinrich for multiday events that were not properly displayed because the first day occurred in the current month, but before the first day included in the list.
1.019:	TWiki:Main.DavidBright: Added support for monthly repeaters specified as "L Fri" (last Friday in all months).
1.018:	TWiki:Main.DavidBright: Added capability to display multiple months in one call, display events in a list, and provided for more extensive formatting of date and description of events.
1.017:	TWiki:Main.DanielRohde: Added start and end date support for periodic repeaters; Added <code>initlang</code> patch by TWiki:Main.JensKloecker; Changed 'my' to 'local' so exceptions working again; Removed <code>fetchxmap</code> debug message; Fixed illegal date bug; Allowed month abbreviations in month attribute
1.016:	TWiki:Main/DavidBright: Added support for anniversary events; changed "our" to "my" in module to support perl versions prior to 5.6.0
1.015:	TWiki:Main.PatriceFournier: Added back support for preview showing unsaved events; Two loop fixes from TWiki:Main.DanielRohde
1.014:	TWiki:Main.NathanKerr: Added start and end date support for weekly repeaters
1.013:	TWiki:Main.MartinCleaver: Added multiple <code>topic=web.topic</code> parameters
1.012:	TWiki:Main/PeterThoeny: Added missing doc of <code>gmtoffset</code> parameter (was deleted in 1.011)
1.011:	TWiki:Main/PeterThoeny: Fixed deep recursion bug; preview shows now unsaved events; performance and resource improvements; documented most of <code>HTML::CalendarMonthSimple</code> attributes; TWiki:Main/PaulineCheung: Fixed uninitialized










	value in join		
1.010:	TWiki:Main/DanBoitnott: Fixed variable conflict in timezone code		
1.009:	TWiki:Main/DanBoitnott: Added ability to have event topics in other webs		
1.008:	TWiki:Main/AnthonPang: Added daynames attribute; TWiki:Main/JensKloecker: Added lang attribute; TWiki:Main/DanBoitnott: Added yearly, monthly, weekly, and periodic events and exceptions		
1.006:	TWiki:Main/DanBoitnott: Added monthly date support		
1.005:	TWiki:Main/AkimDemaille: handle date intervals (thanks!)		
1.004:	uses only HTML::CalendarMonthSimple, ISO dates, all possible settings, fixed month bug		
1.003:	introducing HTML::CalendarMonthSimple		
1.002:	TWiki:Main/ChristianSchultze: highlight today, relative month/year and debugging (thanks!)		
1.001:	delayed load of used packages		
1.000:	first release using only HTML::CalendarMonth		
Dependencies:	Name	Version	Description
	Date::Calc	>=1.000	Required. Download from CPAN:Date::Calc
	HTML::CalendarMonthSimple	>=1.23	Required. Download from CPAN:HTML::CalendarMonthSimple
License:	GPL (GNU General Public License)		
Home:	http://foswiki.org/Extensions/CalendarPlugin		
Support:	http://foswiki.org/Support/CalendarPlugin		

[Edit](#) | [Attach](#) | [Print version](#) | [History: %REVISIONS%](#) | [Backlinks](#) | [Raw View](#) | [More topic actions](#)
 Topic revision: r8 - 08 Feb 2006 - 22:22:32 - ProjectContributor

- ☐ System

- Log In

- **Toolbox**

-  Users
-  Groups
-  Index
-  Search
-  Changes
-  Notifications
-  RSS Feed
-  Statistics
-  Preferences

- **User Reference**

- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**

- Reference Manual
- AdminToolsCategory

- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences
- **Categories**
 - Admin Documentation
 - Admin Tools
 - Developer Doc
 - User Documentation
 - User Tools
- **Webs**
 - ☐ Public
 - ☐ System

-
-



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback