

Table of Contents

Templates for CommentPlugin.....	1
Template definitions.....	1
Templates used in rest of file.....	1
User templates.....	1
top.....	1
bottom.....	2
above.....	2
bulletabove.....	2
threadmode.....	3
belowthreadmode.....	3
below.....	3
tableprepend.....	3
tableappend.....	4
after: Add before the comment box, after the last comment.....	4
action.....	4
table.....	5
toctalk.....	5
bookmark.....	5
return.....	6
Include UserComments.....	6

Templates for CommentPlugin

See CommentPlugin: Customisation for help.

While this topic can be viewed as a topic, it is used by the CommentPlugin as a template file. The syntax is the same as used for the templates used for presentation in skins - see SkinTemplates. The important content in here is in the verbatim blocks. The rest of the topic is just comments.

See CommentPluginExamples to view rendered templates

WARNING: THIS FILE WILL BE OVERWRITTEN WHEN YOU UPGRADE THE COMMENT PLUGIN

Put your local templates into UserCommentsTemplate? (create if it does not exist yet). **Local templates defined in that topic will override templates defined below.**

Template definitions

Note that the use of URLPARAM in the templates should be done in a way that prevents Cross Site Scripting attacks. The safest is to let URLPARAM encode the unsafe characters (default) but this prevents the user from entering Foswiki macros in the comment input fields. It is however safe to use encode="off" when the following rules are observed.

- The encode="off" option for URLPARAM is only used in this topic within verbatim tags to prevent this topic from being an XSS attack vector.
- The encode="off" option is only used in OUTPUT defs and never in the PROMPT.

Templates used in rest of file

Generic prompt box used by other templates

```
%TMPL:DEF{promptbox}%<div class="commentPlugin commentPluginPromptBox"><table border="0" c
```

Short comment, signed and dated

```
%TMPL:DEF{outputoneline}% * %URLPARAM{"comment" encode="off"}% -- %WIKIUSERNAME% - %GMT
```

See rendered template Default

User templates

top

Comments, signed and dated, added at top of file

```
%TMPL:DEF{PROMPT:top}%%TMPL:P{promptbox}%%TMPL:END%
```

```
%TMPL:DEF{OUTPUT:top}%%TMPL:P{outputoneline}%%POS:TOP%
%TMPL:END%
```

See rendered template top

bottom

Comments, signed and dated, added at end of file

```
%TMPL:DEF{PROMPT:bottom}%%TMPL:P{promptbox}%%TMPL:END%

%TMPL:DEF{OUTPUT:bottom}%%POS:BOTTOM%%TMPL:P{outputoneline}%%TMPL:END%
```

See rendered template bottom

above

Comments, signed and dated, added immediately before anchor

```
%TMPL:DEF{PROMPT:above}%%TMPL:P{promptbox}%%TMPL:END%

%TMPL:DEF{OUTPUT:above}%%POS:BEFORE%%TMPL:P{OUTPUT:threadmode}%%TMPL:END%
```

See rendered template above

bulletabove

Bullet item added immediately before anchor. The input field width is passed with parameter `inputsize`, for example:

```
%COMMENT{type="bulletabove" inputsize="20"}%

%TMPL:DEF{PROMPT:bulletabove}%<input class="foswikiInputField" name="bullet_above_item" id=

%TMPL:DEF{OUTPUT:bulletabove}%      * %URLPARAM{"bullet_above_item" encode="off"}%%POS:BEFORE
%TMPL:END%
```

See rendered template bulletabove

threadmode

Wiki thread mode comment, signed and dated

```
%TMPL:DEF{PROMPT:threadmode}%%TMPL:P{promptbox}%%TMPL:END%

%TMPL:DEF{OUTPUT:threadmode}%%POS:BEFORE%

%URLPARAM{"comment" encode="off"}%

-- %WIKIUSERNAME% - %DATE%
%TMPL:END%
```

See rendered template threadmode

belowthreadmode

Comments, signed and dated, added recurse after comment box.

```
%TMPL:DEF{PROMPT:belowthreadmode}%%TMPL:P{promptbox}%%TMPL:END%

%TMPL:DEF{OUTPUT:belowthreadmode}%%POS:AFTER%
---++++ %WIKIUSERNAME% - %SERVERTIME%

%URLPARAM{"comment" encode="off"}%

%TMPL:END%
```

See rendered template belowthreadmode

below

Comments, signed and dated, added immediately below anchor

```
%TMPL:DEF{PROMPT:below}%%TMPL:P{promptbox}%%TMPL:END%

%TMPL:DEF{OUTPUT:below}%%POS:AFTER%%TMPL:P{outputoneline}%%
%TMPL:END%
```

See rendered template below

tableprepend

Comments, signed and dated, added at top of table below the anchor/location/COMMENT

```
%TMPL:DEF{PROMPT:tableprepend}%%TMPL:P{promptbox}%%TMPL:END%
```

```
%TMPL:DEF{OUTPUT:tableprepend}%%POS:AFTER%| %URLPARAM{"comment" newline="<br />" encode="o  
%TMPL:END%
```

See rendered template tableprepend

tableappend

Comments, signed and dated, added at end of table above the anchor/location/COMMENT

```
%TMPL:DEF{PROMPT:tableappend}%%TMPL:P{promptbox}%%TMPL:END%
```

```
%TMPL:DEF{OUTPUT:tableappend}%%POS:BEFORE%| %URLPARAM{"comment" newline="<br />" encode="o  
%TMPL:END%
```

See rendered template tableappend

after: Add before the comment box, after the last comment

```
%TMPL:DEF{PROMPT:after}%%TMPL:P{promptbox}%%TMPL:END%
```

```
%TMPL:DEF{OUTPUT:after}%%NOP%%TMPL:P{outputoneline} %  
%POS:BEFORE%%TMPL:END%
```

See rendered template after

action

Action added to action table directly above comment box (requires Foswiki:Extensions/ActionTrackerPlugin)

```
%TMPL:DEF{PROMPT:action}%
```

```
%TABLE{datavg="#ffffff" tableborder="0" cellborder="0"}%  
| <label for="action_who">Action for</label>| <input class="foswikiInputField" name=  
| <label for="action_due">Due date</label>| <input class="foswikiInputField" name="action_  
| <label for="action_comment">Comment</label>| <textarea %DISABLED% rows="%rows|3%" col  
|| <input %DISABLED% type="submit" class="foswikiButton" value="Add action" /> |  
%TMPL:END%
```

```
%TMPL:DEF{OUTPUT:action}%%POS:BEFORE%%AC%NOP%TION{who="%URLPARAM{"action_who" encode="off"  
%TMPL:END%
```

See rendered template action

table

Table rows adding on end

```
%TMPL:DEF{PROMPT:table}%
%TABLE{datavg="#ffffff" tableborder="0" cellborder="0"}%
|      <label for="comment_date">Date</label>| <input class="foswikiInputField" %DISABLED%
|      <label for="comment_city">City</label>| <input class="foswikiInputField" %DISABLED%
|| <input %DISABLED% type="submit" class="foswikiButton" value="%button|Add entry%" /> |
%TMPL:END%

%TMPL:DEF{OUTPUT:table}%%POS:BEFORE%| %URLPARAM{"comment_date" encode="off"}% | %WIKIUSERN
%TMPL:END%
```

See rendered template table

toctalk

Talk using TOC adding on end

```
%TMPL:DEF{PROMPT:toctalk}%
%TABLE{datavg="#ffffff" tableborder="0" cellborder="0"}%
|      <label for="comment_summary">Summary</label>| <input class="foswikiInputField" %D
|      <label for="toctalk_comment_text">Message</label>| <textarea %DISABLED% rows="%ro
|| <input %DISABLED% type="submit" value="%button|Add%" class="foswikiButton" /> |
%TMPL:END%

%TMPL:DEF{OUTPUT:toctalk}%
%POS:BEFORE%---+++ %SERVERTIME% %WIKIUSERNAME%: %URLPARAM{"comment_summary" encode="off"}%
%POS:BEFORE%%URLPARAM{"toctalk_comment_text" encode="off"}%
%POS:BEFORE%
%TMPL:END%
```

See rendered template toctalk

bookmark

Create a list of annotated bookmarks

```
%TMPL:DEF{PROMPT:bookmark}%
%TABLE{datavg="#ffffff" tableborder="0" cellborder="0"}%
|      <label for="comment_url">Url</label>| <input class="foswikiInputField" %DISABLED%
| <label for="comment_link">Link label</label>| <input class="foswikiInputField" %DISABLED%
|      <label for="bookmark_comment_text">Comment</label>| <input class="foswikiInputField" %
|| <input %DISABLED% type="submit" value="%button|Add bookmark%" class="foswikiButton" />
%TMPL:END%

%TMPL:DEF{OUTPUT:bookmark}%%POS:BEFORE%      * [[%URLPARAM{"comment_url" encode="entity"}%]] [%
%TMPL:END%
```

See rendered template bookmark

return

Post to a different topic and return to here. The comment `target` is set in the `PROMPT`. In the form below the `redirectto` is set to the current (including) topic.

```
%TMPL:DEF{returnpromptbox}%  
<input type="hidden" name="redirectto" value="%BASEWEB%.%BASETOPIC%" />  
%TMPL:P{promptbox}%  
%TMPL:END%  
  
%TMPL:DEF{PROMPT:return}%%TMPL:P{returnpromptbox}%%TMPL:END%  
  
%TMPL:DEF{OUTPUT:return}%%POS:BEFORE%%TMPL:P{OUTPUT:threadmode}%%TMPL:END%
```

See rendered template `return`

Include UserComments

Including `UserCommentsTemplate?` ("`Template`" gets automatically appended to the name):

```
%TMPL:INCLUDE{"UserComments"}%
```

[Edit](#) | [Attach](#) | [Print version](#) | [History: %REVISIONS%](#) | [Backlinks](#) | [Raw View](#) | [More topic actions](#)

Topic revision: `r1` - 17 Dec 2006 - 00:01:48 - [ProjectContributor](#)

- [.System](#)

- [Log In](#)

- **Toolbox**

- [Users](#)
- [Groups](#)
- [Index](#)
- [Search](#)
- [Changes](#)
- [Notifications](#)
- [RSS Feed](#)
- [Statistics](#)
- [Preferences](#)

- **User Reference**

- [BeginnersStartHere](#)
- [TextFormattingRules](#)
- [Macros](#)
- [FormattedSearch](#)
- [QuerySearch](#)

- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**

- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**

- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**

- Public
- System

-
-



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback