

Table of Contents

JQueryRating.....	1
Usage.....	1
Formfield rating.....	1
Examples.....	1

JQueryRating

Homepage: <http://www.fyneworks.com/jquery/star-rating/>

Author(s): Diego A. (Fyneworks.com)

Version: 3.12

The Star Rating Plugin is a plugin for the jQuery Javascript library that creates a non-obstrusive star rating control based on a set of radio input boxes.

It turns a collection of radio boxes into a neat star-rating control. It creates the interface based on standard form elements, which means the basic functionality will still be available even if Javascript is disabled.

Usage

Create a set of radio buttons and surround them with a div of class **jqRating**. When you hover over the stars, a tooltip at the right side will display the value of the radio box, or the title if present.

Formfield rating

The jquery rating plugin is used to implement a **rating** formfield. Here are some examples:

Name	Type	Size	Values	Tooltip message	Attributes
Rating1	rating	10	very low, low, substandard, standard, superior, I like it, quite good, good, very good, excellent		
Rating2	rating	20	0.5, 1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 9.5, 10		split:2
Rating3	rating+values	10	very low=1, low=2, substandard=3, standard=4, superior=5, I like it=6, quite good=7, good=8, very good=9, excellent=10		

- Rating1 defines a simple scheme using named categories.
- Rating2 defines a selection between 0-10 using 0.5 steps
- Rating3 defines a numeric rating where each value is mapped to a named category

Note, that the Attributes column of a rating field will be used to parametrize the jquery rating plugin.

Examples

```
%STARTSECTION{"markup"}%  
<div class="jqRating">  
  <input type="radio" name="test" value="1" class="rating" title="very low"/>  
  <input type="radio" name="test" value="2" class="rating" title="low" />  
  <input type="radio" name="test" value="3" class="rating" title="substandard" />  
</div>
```

```

<input type="radio" name="test" value="4" class="rating" title="standard" />
<input type="radio" name="test" value="5" class="rating" title="superior" checked="checked" />
<input type="radio" name="test" value="6" class="rating" title="I like it" />
<input type="radio" name="test" value="7" class="rating" title="quite good" />
<input type="radio" name="test" value="8" class="rating" title="good" />
<input type="radio" name="test" value="9" class="rating" title="very good" />
<input type="radio" name="test" value="10" class="rating" title="excellent" />
</div>
%ENDSECTION{"markup"}%

```

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions

Topic revision: r4 - 08 Feb 2010 - 22:36:29 - ProjectContributor

- .System

- Log In

- **Toolbox**

- Users
- Groups
- Index
- Search
- Changes
- Notifications
- RSS Feed
- Statistics
- Preferences

- **User Reference**

- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**

- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**

- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**
 - Public
 - System

-
-



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback