

Table of Contents

Search Help.....	1
Search Pages.....	1
Formatted Searches.....	1
Search Preferences.....	1

Search Help

Search Pages

There are two search pages; WebSearch offers basic search features, while WebSearchAdvanced offers more control over searches.

By default searches are keyword based like in a typical search engine:

- Specify word(s) you want to find
- Multiple words form an **AND** search, `intranet web service` returns all pages that have the three words anywhere in the page
- Optionally specify plus signs for **AND** search, like `intranet +web +service`
- Enclose words in double quotes to form a **literal search**, like `"web service"`
- Specify a minus sign to **exclude** a word, like `soap -shampoo`
- Use double quotes if you want to search for a leading minus sign, like `"-nowarn"`
- **Stop words** are excluded from a keyword search:
 - ◆ Stop words are common words and characters such as "how" and "where", defined by the SEARCHSTOPWORDS preference setting
 - ◆ If you want to search for a word in the stop word list, prefix the word with a plus sign
- **Example:** To search for all topics that contain "SOAP", "WSDL", a literal "web service", but not "shampoo",
enter this: `soap +wsdl "web service" -shampoo`

Regular expression search searches for a set of regular expression patterns:

- Patterns are separated by semicolons
- An AND search is performed for the list of patterns
- An exclamation point preceding a pattern indicates an AND NOT search; use it to exclude a pattern, like `!web service`
- If you want to search for a semicolon or an exclamation point, escape them with a leading backslash, like `\!shampoo`
- **Example:** To search for all topics that contain "SOAP", "WSDL", a literal "web service", but not "shampoo",
enter this: `soap;wsdl;web service;!shampoo`

Formatted Searches

You can embed a nicely formatted search in a topic by using the `%SEARCH{ }%` macro described in VarSEARCH.

Search Preferences

The default search preferences are:

- SEARCHDEFAULTTTYPE: Default search type for search forms which calls the search script

- ◆ Currently keyword
- SEARCHVARDEFAULTTYPE: Default search type for %SEARCH{ } macro
 - ◆ Currenty literal
- SEARCHSTOPWORDS: List of stop words (common words and characters to exclude from a keyword search)
 - ◆ Currently a, all, am, an, and, any, as, at, b, be, by, c, d, e, for, from, g, h, how, i, i'm, i.e., in, is, isn't, it, it's, its, j, k, l, m, n, o, of, on, or, p, q, r, s, t, that, that's, the, this, to, u, v, w, was, wasn't, what, what's, when, where, who, who's, will, with, x, y, z

Related Topics: UserDocumentationCategory

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions

Topic revision: r1 - 09 Jan 2009 - 13:00:00 - ProjectContributor

- .System

- Log In

• Toolbox

- Users
- Groups
- Index
- Search
- Changes
- Notifications
- RSS Feed
- Statistics
- Preferences

• User Reference

- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

• Admin Maintenance

- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**

- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**

- Public
- System

-
-



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback