

Table of Contents

SyntaxHighlightingPlugin.....	1
Description.....	1
Syntax Rules.....	2
Using SyntaxHighlightingPlugin With Other Syntax Highlighters.....	2
Examples.....	2
Change of Syntax.....	3
Installation Instructions.....	3
Plugin Files.....	4
Plugin Info.....	4

SyntaxHighlightingPlugin

This Plugin is used to emphasize the rendering of your wiki text according to several languages.

Description

The Syntax Highlighting Plugin is used to emphasize the rendering of your wiki text according to several languages.

It uses `enscript` to render its output.

It supports the following languages :

- ada
- asm
- awk
- bash
- c
- changelog
- c++
- csh
- delphi
- diff
- diffs
- diffu
- elisp
- fortran
- fortran_pp
- haskell
- html
- idl
- inf
- java
- javascript
- ksh
- m4
- mail
- makefile
- maple
- matlab
- modula_2
- nested
- nroff
- objc
- outline
- pascal
- perl
- postscript
- python
- rfc

- scheme
- sh
- skill
- sql
- states
- synopsys
- tcl
- tcsh
- tex
- vba
- verilog
- vhdl
- vrm1
- wmlscript
- zsh

Syntax Rules

To use this plugin, use the following syntax:

```
%CODE{lang="..." [num="10"]} %
...code...
%ENDCODE%
```

The language can be any from the above list. The `num` setting is optional and will set the starting line number.

Using SyntaxHighlightingPlugin With Other Syntax Highlighters

Currently all the Foswiki syntax highlighting plugins use the same `%CODE%` syntax. This allows you to switch the highlighter you use without having to update all your topics to the new syntax. However, it also means that if you have two or more highlighting plugins installed on your system, the plugin that is first in `$Foswiki::cfg{PluginsOrder}` (or by default, first alphabetically) will consume all the `%CODE%` blocks.

Version 1.2 of this plugin added support for using the `%CODE_ENSCRIPT%` syntax, which allows you to explicitly which plugin you want to highlight your code.

Clearly this is not the best solution to the problem of using more than one highlighting plugin. You can read the background on why this approach was taken in the [\[Foswikitask:Item1353\]\[task report\]](#).

Examples

The following text :

```
%CODE{"c++"} %
#include <iostream>
int main()
{
    std::cout << "Hello, world." << std::endl;
}
%ENDCODE%
```

gives (if installed):

```
#include <iostream>
int main()
{
    std::cout << "Hello, world." << std::endl;
}
```

You can also output numbered lines starting at 10 with this text:

```
%CODE{"sh" num="10"}%
#!/bin/sh
languages=`enscript --help-highlight | grep 'Name:' | cut -d ' ' -f 2`
for l in $languages; do
    cat << EOF
    * $l
EOF
done
%ENDCODE%
```

gives (if installed):

```
10#!/bin/sh
11languages=`enscript --help-highlight | grep 'Name:' | cut -d ' ' -f 2`
12for l in $languages; do
13    cat << EOF
14    * $l
15    EOF
16done
```

Change of Syntax

This plugin used to use the following syntax (pre September 2008):

```
%begin sh%
...code...
%end%
```

This has been changed to be more consistent with other Foswiki variables. There is a script included which will replace the old syntax with the new. To use it, copy it from the `tools` directory and into your `data` directory. When you run it, it will look through your webs and replace the syntax. Note that its not the best script in the world, so always test it on a copy of your data first!

Installation Instructions

You do not need to install anything in the browser to use this extension. The following instructions are for the administrator who installs the extension on the server.

Open configure, and open the "Extensions" section. Use "Find More Extensions" to get a list of available extensions. Select "Install".

If you have any problems, or if the extension isn't available in `configure`, then you can still install manually from the command-line. See <http://foswiki.org/Support/ManuallyInstallingExtensions> for more help.

You should ensure the path to `enscript` is correctly set in `configure` before enabling the plugin.

Plugin Files

File:	Description:
<code>data/System/SyntaxHighlightingPlugin.txt</code>	Plugin Topic
<code>lib/Foswiki/Plugins/SyntaxHighlightingPlugin.pm</code>	Perl Module
<code>lib/Foswiki/Plugins/SyntaxHighlightingPlugin/Config.spec</code>	Configure Spec
<code>tools/SyntaxHighlightingPlugin_covert.pl</code>	Script to convert from old syntax to new

Plugin Info

Plugin Author(s):	Foswiki:Main.AndrewJones		
Previous Author(s):	TWiki:Main.NicolasTisserand, TWiki:Main.NicolasBurrus, Perceval Anichini		
Copyright:	© 2008 - 2009, Andrew Jones, © 2000 - 2001, Andrea Sterbini, © 2001, Peter Theony		
License:	GPL (GNU General Public License)		
Plugin Release:	1.2		
Plugin Version:	4052 (2009-06-07)		
Change History:			
07 Jun 2009:	1.2: Fixed rendering in numbered lists (Foswikitask:Item8176); Moved <code>configure</code> setting to Extensions heading -- Foswiki:Main.AndrewJones		
29 Mar 2009:	1.1: Added <code>%CODE_ENSCRIPT%</code> syntax so it can be used with other syntax highlighters (Foswikitask:Item1353) -- Foswiki:Main.AndrewJones		
17 Mar 2009:	1.0: Initial release for Foswiki (Foswikitask:Item1251) -- Foswiki:Main.AndrewJones		
11 Sep 2008:	Rewritten to work on TWiki 4.2 (TWikibug:Item5995) -- Foswiki:Main.AndrewJones		
12 Jul 2002:	Initial version		
Dependencies:	Name	Version	Description
	IPC::Run	>0	Required
	enscript	>1.6.4	Required. Known to work with version 1.6.4 and not with 1.6.1
Plugin Home:	http://foswiki.org/Extensions/SyntaxHighlightingPlugin		
Support:	http://foswiki.org/Support/SyntaxHighlightingPlugin		

Related Topics: DefaultPreferences, SitePreferences, Plugins

This topic: System > SyntaxHighlightingPlugin

Topic revision: r1 - 22 Jun 2007 - 23:25:52 - ProjectContributor



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? [Send feedback](#)