

Table of Contents

VarMETA.....	1
META -- displays meta-data.....	1

VarMETA

You are here: Wiki >System Web>VarMETA (09 Jan 2009, ProjectContributor)EditAttach

META -- displays meta-data

- Provided mainly for use in templates, this macro generates the parts of the topic view that relate to meta-data (attachments, forms etc.) The `formfield` item is the most likely to be useful to casual users.
- Syntax: `%META{ "item" ...}%`
- Parameters:

Item	Options	Description
"formfield"	<code>name="..."</code> : name of the field. The field value can be shortened as described in FormattedSearch for <code>\$formfield</code> <code>newline="..."</code> : by default, each newline character will be rewritten to <code>
</code> to allow metadata that contains newlines to be used in tables, etc. <code>\$n</code> indicates a newline character. <code>bar="..."</code> : by default, each vertical bar is rewritten to an HTML entity so as to not be mistaken for a table separator.	Show a single form field
"form"	<i>none</i>	Generates the table showing the form fields. See Form Definition
"attachments"	<code>all="on"</code> to show hidden attachments. <code>title="..."</code> to show a title - only if attachments are displayed. <code>template="..."</code> to use a custom template for the rendering of attachments; default <code>attachables</code> is used.	Generates the list of attachments
"moved"	<i>none</i>	Details of any topic moves
"parent"	<code>dontrecurse="on"</code> : By default recurses up tree, this has some cost. Equivalent to <code>depth=1</code> <code>depth="..."</code> : Return only the specified ancestor. <code>nowebhome="on"</code> : Suppress WebHome. <code>prefix="..."</code> : Prefix that goes before parents, but only if there are parents, default <code>" "</code> . <code>format="..."</code> : Format string used to display each parent topic where <code>\$web</code> expands to the web name, and <code>\$topic</code> expands to the topic name; default: <code>" [[\$web.\$topic] [\$topic]] "</code> <code>suffix="..."</code> : Suffix, only appears if there are parents; default <code>" "</code> . <code>separator="..."</code> : Separator between parents; default <code>" > "</code> .	Generates the parent link

- Related: METASEARCH

Edit | Attach | Print version | History: `%REVISIONS%` | Backlinks | Raw View | More topic actions
Topic revision: r1 - 09 Jan 2009 - 13:00:00 - ProjectContributor

- ☐ System

- Log In

- **Toolbox**

-  Users
-  Groups
-  Index
-  Search
-  Changes
-  Notifications
-  RSS Feed
-  Statistics
-  Preferences

- **User Reference**

- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**

- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**

- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**

- ☐ Public
- ☐ System

-
-



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback