

Table of Contents

Var QUERYPARAMS.....	1
QUERYPARAMS -- show paramaters to the query.....	1

VarQUERYPARAMS

You are here: Wiki >System Web>VarQUERYPARAMS (09 Jan 2009, ProjectContributor)EditAttach


QUERYPARAMS -- show paramaters to the query

- Expands the parameters to the query that was used to display the page.
- Syntax: %QUERYPARAMS{...}%
- Supported parameters:









Parameter:▲	Description:	Default:
encoding="entity" encoding="safe" encoding="html" encoding="quotes" encoding="url"	Control how special characters are encoded. If this parameter is not given, "safe" encoding is performed which HTML entity encodes the characters ' "<>%. entity: Encode special characters into HTML entities, like a double quote into ". Does not encode \n or \r. safe: Encode characters ' "<>% into HTML entities. (this is the default) html: As type="entity" except it also encodes \n and \r quotes: Escape double quotes with backslashes (\ "), does not change other characters url: Encode special characters for URL parameter use, like a double quote into %22	type="safe"
format="..."	Format string for each entry	\$name=\$value
separator="..."	Separator string	separator="\$n" (newline)

- The following escape sequences are expanded in the format string:

Sequence:	Expands To:
\$name	Name of the parameter
\$value	String value of the parameter. Multi-valued parameters will have a "row" for each value.
\$n or \$n()	New line. Use \$n() if followed by alphanumeric character, e.g. write Foo\$n() Bar instead of Foo\$nBar
\$nop or \$nop()	Is a "no operation". This token gets removed; useful for nested search
\$quot	Double quote (") (\ " also works)
\$percnt	Percent sign (%)
\$dollar	Dollar sign (\$)
\$lt	Less than sign (<)
\$gt	Greater than sign (>)
\$amp	Ampersand (&)

- Example:
 - ◆ `%QUERYPARAMS{format="<input type='hidden' name='$name' value='$value' encoding="entity" />"}`
-  **Security warning!**
 Using QUERYPARAMS can easily be misused for cross-site scripting unless specific characters are entity encoded. By default QUERYPARAMS encodes the characters ' "<>% into HTML entities (same as encoding="safe") which is relatively safe. The safest is to use encoding="entity". When passing QUERYPARAMS inside another macro always use double quotes (") combined with using QUERYPARAMS with encoding="quote". For maximum security against cross-site scripting you are advised to install the Foswiki:Extensions.SafeWikiPlugin.
- See also QUERYSTRING, URLPARAM

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions
 Topic revision: r1 - 09 Jan 2009 - 13:00:00 - ProjectContributor

-  System
- Log In
- **Toolbox**
 -  Users
 -  Groups
 -  Index
 -  Search
 -  Changes
 -  Notifications
 -  RSS Feed
 -  Statistics
 -  Preferences
- **User Reference**
 - BeginnersStartHere
 - TextFormattingRules
 - Macros
 - FormattedSearch
 - QuerySearch
 - DocumentGraphics
 - SkinBrowser
 - InstalledPlugins
- **Admin Maintenance**
 - Reference Manual
 - AdminToolsCategory
 - InterWikis
 - ManagingWebs
 - SiteTools
 - DefaultPreferences
 - WebPreferences
- **Categories**
 - Admin Documentation
 - Admin Tools
 - Developer Doc

- User Documentation
- User Tools

- **Webs**
- ☐ Public
- ☐ System

•
•



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback