Table of Contents

VarTABLE.....1
TABLE{ attributes } -- control attributes of tables and sorting of table columns.....1

VarTABLE

You are here: Wiki >System Web>VarTABLE (07 Oct 2007, ProjectContributor)EditAttach

TABLE{ *attributes* } -- control attributes of tables and sorting of table columns

- The `%TABLE{}%` macro is handled by the TablePlugin
- Syntax: `%TABLE{ attributes }%`

- Supported attributes:

Argument	Comment	Default value	Example
`sort`	Set table sorting by clicking headers `"on"` or `"off"`.	unspecified	`sort="on"`
`initsort`	Column to sort initially (`"1"` to number of columns).	unspecified	`initsort="2"`
`initdirection`	Initial sorting direction for `initsort`, set to `"up"` (descending) or `"down"` (ascending).	unspecified	`initdirection="up"`
`disableallsort`	Disable all sorting, both initsort and header sort. This is mainly used by plugins such as the EditTablePlugin to disable sorting in a table while editing the table.	unspecified	`disableallsort="on"`
`headerbg`	Header cell background colour.	`"#6b7f93"`	`headerbg="#999999"`
`headerbgsorted`	Header cell background colour of a sorted column.	the value of `headerbg`	`headerbgsorted="#32596c"`
`headercolor`	Header cell text colour.	`"#ffffff"`	`headercolor="#0000cc"`
`databg`	Data cell background colour, a comma separated list. Specify `"none"` for no colour, that is to use the colour/background of the page the	`"#edf4f9,#ffffff"`	`databg="#f2f2f2,#ffffff"`

Argument	Comment	Default value	Example
	table is on.		
databgsorted	Data cell background colour of a sorted column; see databg.	the values of databg	databgsorted="#d4e8e4,#e5f5e
datacolor	Data cell text colour, a comma separated list.	unspecified	datacolor="#0000CC, #000000"
tableborder	Table border width (pixels).	"1"	tableborder="2"
tableframe	Table frame, set to "void" (no sides), "above" (the top side only), "below" (the bottom side only), "hsides" (the top and bottom sides only), "lhs" (the left-hand side only), "rhs" (the right-hand side only), "vsides" (the right and left sides only), "box" (all four sides), "border" (all four sides).	unspecified	tableframe="hsides"
tablerules	Table rules, set to "none" (no rules), "groups" (rules will appear between row groups and column groups only), "rows" (rules will appear between rows only), "cols" (rules will appear between columns only), "all" (rules will appear between all rows and columns).	unspecified	tablerules="rows"
cellpadding	Cell padding (pixels).	"0"	cellpadding="0"
cellspacing	Cell spacing (pixels).	"0"	cellspacing="3"
cellborder	Cell border width (pixels).	unspecified	cellborder="0"
valign	Vertical alignment of cells and	unspecified	valign="top"

Argument	Comment	Default value	Example
	headers, set to "top", "middle", "bottom" or "baseline".		
headervalign	Vertical alignment of header cells; overrides valign.	unspecified	headervalign="top"
datavalign	Vertical alignment of data cells; overrides valign.	unspecified	datavalign="top"
headeralign	Header cell alignment, one value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.	unspecified	headeralign="left,right"
dataalign	Data cell alignment, one value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.	unspecified	dataalign="center"
tablewidth	Table width: Percentage of window width, or absolute pixel value.	unspecified	tablewidth="100%"
columnwidths	Column widths: Comma delimited list of column widths, percentage or absolute pixel	unspecified	columnwidths="80%,20%"

Argument	Comment	Default value	Example
	value.		
`headerrows`	Number of header rows to exclude from sort. (will be rendered in a HTML `thead` section)	`"1"`	`headerrows="1"`
`footerrows`	Number of footer rows to exclude from sort. (will be rendered in a HTML `tfoot` section)	`"0"`	`footerrows="1"`
`id`	Unique table identifier string, used for targeting a table with CSS.	`tableN` (where N is the table order number on the page)	`id="userTable"`
`summary`	Table summary used by screenreaders: A summary of what the table presents. It should provide an orientation for someone who listens to the table.	unspecified	`summary="List of subscribed users"`
`caption`	Table caption: A title that will be displayed just above the table.	unspecified	`caption="Users"`

- Example:
```
%TABLE{ tableborder="0" cellpadding="4" cellspacing="3"
cellborder="0" }%
| *A1* | *B1* |
| A2 | B2 |
```
- Related: See TablePlugin for more details

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions
Topic revision: r0 - 07 Oct 2007 - 06:09:24 - ProjectContributor

- System

- Log In

- **Toolbox**
- Users
- Groups
- Index
- Search
- Changes
- Notifications

- RSS Feed
- Statistics
- Preferences

- **User Reference**
- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**
- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**
- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**
- Public
- System

Copyright © by the contributing authors. All material on this site is the property of the contributing authors.
Ideas, requests, problems regarding Wiki? Send feedback