

Table of Contents

VarTABLE.....	1
TABLE{ attributes } -- control attributes of tables and sorting of table columns.....	1

VarTABLE

You are here: Wiki >System Web>VarTABLE (07 Oct 2007, ProjectContributor)EditAttach

TABLE{ *attributes* } -- control attributes of tables and sorting of table columns

- The %TABLE{ }% macro is handled by the TablePlugin
- Syntax: %TABLE{ *attributes* }%

- Supported attributes:

Argument	Comment ▾	Default value	Example
cellborder	Cell border width (pixels).	unspecified	cellborder="0"
cellpadding	Cell padding (pixels).	"0"	cellpadding="0"
cellspacing	Cell spacing (pixels).	"0"	cellspacing="3"
initsort	Column to sort initially ("1" to number of columns).	unspecified	initsort="2"
columnwidths	Column widths: Comma delimited list of column widths, percentage or absolute pixel value.	unspecified	columnwidths="80%, 20%"
dataalign	Data cell alignment, one value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.	unspecified	dataalign="center"
databgsorted	Data cell background colour of a sorted column; see databg.	the values of databg	databgsorted="#d4e8e4, #e5f5e0
databg	Data cell background colour,	"#edf4f9, #ffffff"	databg="#f2f2f2, #ffffff"

Argument	Comment▲	Default value	Example
	a comma separated list. Specify "none" for no colour, that is to use the colour/background of the page the table is on.		
datacolor	Data cell text colour, a comma separated list.	unspecified	datacolor="#0000CC, #000000"
disableallsort	Disable all sorting, both init sort and header sort. This is mainly used by plugins such as the EditTablePlugin to disable sorting in a table while editing the table.	unspecified	disableallsort="on"
headeralign	Header cell alignment, one value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.	unspecified	headeralign="left, right"
headerbgsorted	Header cell background colour of a sorted column.	the value of headerbg	headerbgsorted="#32596C"
headerbg	Header cell background colour.	"#6b7f93"	headerbg="#999999"
headercolor	Header cell text colour.	"#ffffff"	headercolor="#0000cc"
initdirection	Initial sorting direction for init sort, set to "up" (descending) or "down" (ascending).	unspecified	initdirection="up"
footerrows	Number of footer rows to exclude from sort. (will be rendered in a	"0"	footerrows="1"

Argument	Comment▲	Default value	Example
	HTML tfoot section)		
headerrows	Number of header rows to exclude from sort. (will be rendered in a HTML thead section)	"1"	headerrows="1"
sort	Set table sorting by clicking headers "on" or "off".	unspecified	sort="on"
tableborder	Table border width (pixels).	"1"	tableborder="2"
caption	Table caption: A title that will be displayed just above the table.	unspecified	caption="Users"
tableframe	Table frame, set to "void" (no sides), "above" (the top side only), "below" (the bottom side only), "hsides" (the top and bottom sides only), "lhs" (the left-hand side only), "rhs" (the right-hand side only), "vsides" (the right and left sides only), "box" (all four sides), "border" (all four sides).	unspecified	tableframe="hsides"
tablerules	Table rules, set to "none" (no rules), "groups" (rules will appear between row groups and column groups only), "rows" (rules will appear between rows only), "cols" (rules will appear between columns only), "all" (rules will appear between all rows and columns).	unspecified	tablerules="rows"
summary		unspecified	

Argument	Comment▲	Default value	Example
	Table summary used by screenreaders: A summary of what the table presents. It should provide an orientation for someone who listens to the table.		summary="List of subscribed users"
tablewidth	Table width: Percentage of window width, or absolute pixel value.	unspecified	tablewidth="100%"
id	Unique table identifier string, used for targeting a table with CSS.	tableN (where N is the table order number on the page)	id="userTable"
valign	Vertical alignment of cells and headers, set to "top", "middle", "bottom" or "baseline".	unspecified	valign="top"
data valign	Vertical alignment of data cells; overrides valign.	unspecified	data valign="top"
headervalign	Vertical alignment of header cells; overrides valign.	unspecified	headervalign="top"

- Example:

```
%TABLE{ tableborder="0" cellpadding="4" cellspacing="3"
cellborder="0" }%
| *A1* | *B1* |
| A2 | B2 |
```

- Related: See TablePlugin for more details

[Edit](#) | [Attach](#) | [Print version](#) | [History: %REVISIONS%](#) | [Backlinks](#) | [Raw View](#) | [More topic actions](#)
 Topic revision: r0 - 07 Oct 2007 - 06:09:24 - ProjectContributor

- System

- Log In

- **Toolbox**

-  Users
-  Groups
-  Index
-  Search
-  Changes

-  Notifications
-  RSS Feed
-  Statistics
-  Preferences

• User Reference

- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

• Admin Maintenance

- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

• Categories

- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

• Webs

- Public
- System

•

•



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback