

Table of Contents

VarTABLE.....	1
TABLE{ attributes } -- control attributes of tables and sorting of table columns.....	1

VarTABLE

You are here: Wiki >System Web>VarTABLE (07 Oct 2007, ProjectContributor)EditAttach

TABLE{ *attributes* } -- control attributes of tables and sorting of table columns

- The %TABLE{ }% macro is handled by the TablePlugin
- Syntax: %TABLE{ *attributes* }%

- Supported attributes:

Argument	Comment	Default value▲	Example
sort	Set table sorting by clicking headers "on" or "off".	unspecified	sort="on"
initsort	Column to sort initially ("1" to number of columns).	unspecified	initsort="2"
initdirection	Initial sorting direction for initsort, set to "up" (descending) or "down" (ascending).	unspecified	initdirection="up"
disableallsort	Disable all sorting, both initsort and header sort. This is mainly used by plugins such as the EditTablePlugin to disable sorting in a table while editing the table.	unspecified	disableallsort="on"
datacolor	Data cell text colour, a comma separated list.	unspecified	datacolor="#0000CC, #000000"
tableframe	Table frame, set to "void" (no sides), "above" (the top side only), "below" (the bottom side only), "hsides" (the top and bottom sides only), "lhs" (the left-hand side only), "rhs" (the right-hand side only), "vsides" (the right and left	unspecified	tableframe="hsides"

Argument	Comment	Default value▲	Example
	sides only), "box" (all four sides), "border" (all four sides).		
tablerules	Table rules, set to "none" (no rules), "groups" (rules will appear between row groups and column groups only), "rows" (rules will appear between rows only), "cols" (rules will appear between columns only), "all" (rules will appear between all rows and columns).	unspecified	tablerules="rows"
cellborder	Cell border width (pixels).	unspecified	cellborder="0"
valign	Vertical alignment of cells and headers, set to "top", "middle", "bottom" or "baseline".	unspecified	valign="top"
headervalign	Vertical alignment of header cells; overrides valign.	unspecified	headervalign="top"
datavalign	Vertical alignment of data cells; overrides valign.	unspecified	datavalign="top"
headeralign	Header cell alignment, one value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.	unspecified	headeralign="left, right"
dataalign		unspecified	dataalign="center"

Argument	Comment	Default value▲	Example
	Data cell alignment, one value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.		
tablewidth	Table width: Percentage of window width, or absolute pixel value.	unspecified	tablewidth="100%"
columnwidths	Column widths: Comma delimited list of column widths, percentage or absolute pixel value.	unspecified	columnwidths="80%, 20%"
summary	Table summary used by screenreaders: A summary of what the table presents. It should provide an orientation for someone who listens to the table.	unspecified	summary="List of subscribed users"
caption	Table caption: A title that will be displayed just above the table.	unspecified	caption="Users"
headerbg	Header cell background colour.	"#6b7f93"	headerbg="#999999"
databg	Data cell background colour, a comma separated list. Specify "none" for no colour, that is to use the colour/background of the page the table is on.	"#edf4f9, #ffffff"	databg="#f2f2f2, #ffffff"
headercolor		"#ffffff"	headercolor="#0000cc"

Argument	Comment	Default value▲	Example
	Header cell text colour.		
cellpadding	Cell padding (pixels).	"0"	cellpadding="0"
cellspacing	Cell spacing (pixels).	"0"	cellspacing="3"
footerrows	Number of footer rows to exclude from sort. (will be rendered in a HTML <code>tfoot</code> section)	"0"	footerrows="1"
tableborder	Table border width (pixels).	"1"	tableborder="2"
headerrows	Number of header rows to exclude from sort. (will be rendered in a HTML <code>thead</code> section)	"1"	headerrows="1"
id	Unique table identifier string, used for targeting a table with CSS.	tableN (where N is the table order number on the page)	id="userTable"
headerbgsorted	Header cell background colour of a sorted column.	the value of headerbg	headerbgsorted="#32596c"
databgsorted	Data cell background colour of a sorted column; see <code>databg</code> .	the values of databg	databgsorted="#d4e8e4, #e5f5e0"

- Example:

```
%TABLE{ tableborder="0" cellpadding="4" cellspacing="3"
cellborder="0" }%
| *A1* | *B1* |
| A2 | B2 |
```

- Related: See TablePlugin for more details

[Edit](#) | [Attach](#) | [Print version](#) | [History: %REVISIONS%](#) | [Backlinks](#) | [Raw View](#) | [More topic actions](#)
Topic revision: r0 - 07 Oct 2007 - 06:09:24 - ProjectContributor

- System

- Log In

- **Toolbox**

- Users
- Groups
- Index
- Search
- Changes

-  Notifications
-  RSS Feed
-  Statistics
-  Preferences

• User Reference

- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

• Admin Maintenance

- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

• Categories

- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

• Webs

- Public
- System

•

•



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback