

Table of Contents

VarTABLE.....	1
TABLE{ attributes } -- control attributes of tables and sorting of table columns.....	1

VarTABLE

You are here: Wiki >System Web>VarTABLE (07 Oct 2007, ProjectContributor)EditAttach

TABLE{ *attributes* } -- control attributes of tables and sorting of table columns

- The %TABLE{ }% macro is handled by the TablePlugin
- Syntax: %TABLE{ *attributes* }%

- Supported attributes:

Argument▲	Comment	Default value	Example
caption	Table caption: A title that will be displayed just above the table.	unspecified	caption="Users"
cellborder	Cell border width (pixels).	unspecified	cellborder="0"
cellpadding	Cell padding (pixels).	"0"	cellpadding="0"
cellspacing	Cell spacing (pixels).	"0"	cellspacing="3"
columnwidths	Column widths: Comma delimited list of column widths, percentage or absolute pixel value.	unspecified	columnwidths="80%, 20%"
dataalign	Data cell alignment, one value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.	unspecified	dataalign="center"
databg	Data cell background colour, a comma separated list. Specify "none" for no colour, that is to	"#edf4f9, #ffffff"	databg="#f2f2f2, #ffffff"

Argument	Comment	Default value	Example
	use the colour/background of the page the table is on.		
databgsorted	Data cell background colour of a sorted column; see databg.	the values of databg	databgsorted="#d4e8e4, #e5f5e0
datacolor	Data cell text colour, a comma separated list.	unspecified	datacolor="#0000CC, #000000"
datavalign	Vertical alignment of data cells; overrides valign.	unspecified	datavalign="top"
disableallsort	Disable all sorting, both initSort and header sort. This is mainly used by plugins such as the EditTablePlugin to disable sorting in a table while editing the table.	unspecified	disableallsort="on"
footerrows	Number of footer rows to exclude from sort. (will be rendered in a HTML tfoot section)	"0"	footerrows="1"
headeralign	Header cell alignment, one value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.	unspecified	headeralign="left, right"
headerbg	Header cell background colour.	"#6b7f93"	headerbg="#999999"
headerbgsorted	Header cell background colour of a sorted column.	the value of headerbg	headerbgsorted="#32596c"
headercolor	Header cell text colour.	"#fffffff"	headercolor="#0000cc"

Argument	Comment	Default value	Example
headerrows	Number of header rows to exclude from sort. (will be rendered in a HTML <code>thead</code> section)	"1"	<code>headerrows="1"</code>
headervalign	Vertical alignment of header cells; overrides <code>valign</code> .	unspecified	<code>headervalign="top"</code>
id	Unique table identifier string, used for targeting a table with CSS.	<code>tableN</code> (where N is the table order number on the page)	<code>id="userTable"</code>
initdirection	Initial sorting direction for <code>initsort</code> , set to "up" (descending) or "down" (ascending).	unspecified	<code>initdirection="up"</code>
initsort	Column to sort initially ("1" to number of columns).	unspecified	<code>initsort="2"</code>
sort	Set table sorting by clicking headers "on" or "off".	unspecified	<code>sort="on"</code>
summary	Table summary used by screenreaders: A summary of what the table presents. It should provide an orientation for someone who listens to the table.	unspecified	<code>summary="List of subscribed users"</code>
tableborder	Table border width (pixels).	"1"	<code>tableborder="2"</code>
tableframe	Table frame, set to "void" (no sides), "above" (the top side only), "below" (the bottom side only), "hsides" (the top and bottom sides only), "lhs" (the left-hand side only), "rhs" (the right-hand side only), "vsides" (the right and left sides only), "box" (all four sides),	unspecified	<code>tableframe="hsides"</code>

Argument	Comment	Default value	Example
	"border" (all four sides).		
tablerules	Table rules, set to "none" (no rules), "groups" (rules will appear between row groups and column groups only), "rows" (rules will appear between rows only), "cols" (rules will appear between columns only), "all" (rules will appear between all rows and columns).	unspecified	tablerules="rows"
tablewidth	Table width: Percentage of window width, or absolute pixel value.	unspecified	tablewidth="100%"
valign	Vertical alignment of cells and headers, set to "top", "middle", "bottom" or "baseline".	unspecified	valign="top"

- Example:

```
%TABLE{ tableborder="0" cellpadding="4" cellspacing="3"
cellborder="0" }%
| *A1* | *B1* |
| A2 | B2 |
```

- Related: See TablePlugin for more details

[Edit](#) | [Attach](#) | [Print version](#) | [History: %REVISIONS%](#) | [Backlinks](#) | [Raw View](#) | [More topic actions](#)
 Topic revision: r0 - 07 Oct 2007 - 06:09:24 - ProjectContributor

- System

- Log In

- **Toolbox**

-  Users
-  Groups
-  Index
-  Search
-  Changes

-  Notifications
-  RSS Feed
-  Statistics
-  Preferences

• User Reference

- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

• Admin Maintenance

- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

• Categories

- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

• Webs

- Public
- System

•

•



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback