

Table of Contents

VarTABLE.....	1
TABLE{ attributes } -- control attributes of tables and sorting of table columns.....	1

VarTABLE

You are here: Wiki >System Web>VarTABLE (07 Oct 2007, ProjectContributor)EditAttach

TABLE{ *attributes* } -- control attributes of tables and sorting of table columns

- The %TABLE{ }% macro is handled by the TablePlugin
- Syntax: %TABLE{ *attributes* }%

- Supported attributes:

Argument▼	Comment	Default value	Example
valign	Vertical alignment of cells and headers, set to "top", "middle", "bottom" or "baseline".	unspecified	valign="top"
tablewidth	Table width: Percentage of window width, or absolute pixel value.	unspecified	tablewidth="100%"
tablerules	Table rules, set to "none" (no rules), "groups" (rules will appear between row groups and column groups only), "rows" (rules will appear between rows only), "cols" (rules will appear between columns only), "all" (rules will appear between all rows and columns).	unspecified	tablerules="rows"
tableframe	Table frame, set to "void" (no sides), "above" (the top side only), "below" (the bottom side only), "hsides" (the top and bottom sides only), "lhs" (the left-hand side	unspecified	tableframe="hsides"

Argument	Comment	Default value	Example
	only), "rhs" (the right-hand side only), "vsides" (the right and left sides only), "box" (all four sides), "border" (all four sides).		
tableborder	Table border width (pixels).	"1"	tableborder="2"
summary	Table summary used by screenreaders: A summary of what the table presents. It should provide an orientation for someone who listens to the table.	unspecified	summary="List of subscribed users"
sort	Set table sorting by clicking headers "on" or "off".	unspecified	sort="on"
initsort	Column to sort initially ("1" to number of columns).	unspecified	initsort="2"
initdirection	Initial sorting direction for initsort, set to "up" (descending) or "down" (ascending).	unspecified	initdirection="up"
id	Unique table identifier string, used for targeting a table with CSS.	tableN (where N is the table order number on the page)	id="userTable"
headervalign	Vertical alignment of header cells; overrides valign.	unspecified	headervalign="top"
headerrows	Number of header rows to exclude from sort. (will be rendered in a HTML thead section)	"1"	headerrows="1"
headercolor	Header cell text colour.	"#ffffff"	headercolor="#0000cc"
headerbgsorted	Header cell background colour of a sorted column.	the value of headerbg	headerbgsorted="#32596c"
headerbg	Header cell background colour.	"#6b7f93"	headerbg="#999999"

Argument	Comment	Default value	Example
headeralign	Header cell alignment, one value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.	unspecified	headeralign="left, right"
footerrows	Number of footer rows to exclude from sort. (will be rendered in a HTML tfoot section)	"0"	footerrows="1"
disableallsort	Disable all sorting, both initsort and header sort. This is mainly used by plugins such as the EditTablePlugin to disable sorting in a table while editing the table.	unspecified	disableallsort="on"
dataalign	Vertical alignment of data cells; overrides valign.	unspecified	dataalign="top"
datacolor	Data cell text colour, a comma separated list.	unspecified	datacolor="#0000CC, #000000"
databgsorted	Data cell background colour of a sorted column; see databg.	the values of databg	databgsorted="#d4e8e4, #e5f5e5"
databg	Data cell background colour, a comma separated list. Specify "none" for no colour, that is to use the colour/background of the page the table is on.	"#edf4f9, #ffffff"	databg="#f2f2f2, #ffffff"
dataalign	Data cell alignment, one	unspecified	dataalign="center"

TABLE{ attributes } -- control attributes of tables and sorting of tablecolumns

Argument▼	Comment	Default value	Example
	value for all columns, or a comma separated list for different alignment of individual columns. Set to "left", "center", "right" or "justify". Overrides individual cell settings.		
columnwidths	Column widths: Comma delimited list of column widths, percentage or absolute pixel value.	unspecified	columnwidths="80%,20%"
cellspacing	Cell spacing (pixels).	"0"	cellspacing="3"
cellpadding	Cell padding (pixels).	"0"	cellpadding="0"
cellborder	Cell border width (pixels).	unspecified	cellborder="0"
caption	Table caption: A title that will be displayed just above the table.	unspecified	caption="Users"

- **Example:**

```
%TABLE{ tableborder="0" cellpadding="4" cellspacing="3"
cellborder="0" }%
| *A1* | *B1* |
| A2 | B2 |
```







- **Related:** See TablePlugin for more details

Edit | Attach | Print version | History: %REVISIONS% | Backlinks | Raw View | More topic actions
Topic revision: r0 - 07 Oct 2007 - 06:09:24 - ProjectContributor

- ☐ System

- Log In

- **Toolbox**

-  Users
-  Groups
-  Index
-  Search
-  Changes
-  Notifications

-  RSS Feed
-  Statistics
-  Preferences

- **User Reference**

- BeginnersStartHere
- TextFormattingRules
- Macros
- FormattedSearch
- QuerySearch
- DocumentGraphics
- SkinBrowser
- InstalledPlugins

- **Admin Maintenance**

- Reference Manual
- AdminToolsCategory
- InterWikis
- ManagingWebs
- SiteTools
- DefaultPreferences
- WebPreferences

- **Categories**

- Admin Documentation
- Admin Tools
- Developer Doc
- User Documentation
- User Tools

- **Webs**

- ☐ Public
- ☐ System

-
-



Copyright © by the contributing authors. All material on this site is the property of the contributing authors.

Ideas, requests, problems regarding Wiki? Send feedback